SC90® Platform



Portable Platform

The SC90° Platform is the cornerstone of Sightline Commercial Solutions' portable equipment line. This single-sided, portable platform is well-known throughout multiple markets for its strength, versatility, and durability. SC90° platforms are constructed of structural 1, grade 1 plywood and are intended for interior use or temporary use outdoors protected from rainfall and direct sunlight. The semi-permanent platform features an aluminum extruded frame and with the plywood's aluminum backer, provides a Class A fire rating. It is recommended to store these platforms in an indoor temperature-controlled environment when not in use to prolong the use of the platforms.



SC90® Platform



Portable Platform

Dimensions, Weights, and Surface Options

	4' x 8'	4' x 6'	4' x 4'	3′ x 8′	3′ x 6′	2' x 8'	3.28' x 6.56'
	(1.22m x 2.44m)	(1.22m x 1.83m)	(1.22m x 1.22m)	(0.92m x 2.44m)	(0.92m x 1.83m)	(0.61m x 2.44m)	(1m x 2m)
HDPE Surface	141 lbs	110 lbs	78 lbs	111 lbs	86 lbs	83 lbs	99 lbs
(black or gray)	64 kg	49.9 kg	35.4 kg	35.4 kg	39 kg	37.6 kg	44.9 kg
Carpet Surface	141 lbs	110 lbs	78 lbs	111 lbs	86 lbs	83 lbs	99 lbs
(black)	64 kg	49.9 kg	35.4 kg	35.4 kg	39 kg	37.6 kg	44.9 kg
Unfinished	141 lbs	110 lbs	78 lbs	111 lbs	86 lbs	83 lbs	99 lbs
Plywood Surface	64 kg	49.9 kg	35.4 kg	35.4 kg	39 kg	37.6 kg	44.9 kg
Painted	141 lbs	110 lbs	78 lbs	111 lbs	86 lbs	83 lbs	99 lbs
Plywood Surface	64 kg	49.9 kg	35.4 kg	35.4 kg	39 kg	37.6 kg	44.9 kg
Plyron Surface	158 lbs	122 lbs	86 lbs	125 lbs	97 lbs	93 lbs	112 lbs
	71.7 kg	55.3 kg	349 kg	56.7 kg	44 kg	42.2 kg	50.8 kg
Hardwood	161 lbs	125 lbs	88 lbs	126 lbs	97 lbs	93 lbs	112 lbs
	73 kg	56.7 kg	39.9 kg	57.2 kg	44 kg	42.2 kg	50.8 kg





Carpet



Plyron (Tempered Hardboard)



Tongue & Groove Hardwood Surface











Tech Specifications

Edging: 4" (101.6 mm) high, extruded 6005A-T61 aluminum frame, including

protective edge, mill finish. Built-in Roto-Lock system.

Subfloor: 1" (25.4 mm) exterior rated, group 1 plywood.

· Finished surface: HDPE (black or gray), commercial grade carpet (black), unfinished plywood, painted plywood (black), Plyron (tempered hardboard),

acrylic (clear or opaque)

 \cdot Tongue and groove hardwood surface available upon request (specify wood

species)

Loading: Platform will support 150 lbs/square foot of uniformly distributed live load.

Usage: Singled-sided platform is intended for interior use and temporary use

outdoors protected from rainfall and direct sunlight.

Support & Accessories: For use with all of Sightline Commercial Solutions supports.

· Guardrails · Closure panels · Step units

 \cdot Structural locking clip system \cdot Chair stops \cdot Skirting clips